

REAR LED LIGHT SYSTEMS

DL16/CV & DL16V/CV 4-HEAD ADJUSTABLE REAR LED LIGHT SYSTEMS



**DL16V
STANDARD LED'S**



**DL16
HIGH INTENSITY GEN-3 LED'S**



THE DL16 SERIES IS EXPANDABLE UP TO 8 1/2" IN LENGTH!

Interior mount only to any vehicles rear window deck

Flashback hood

Expandable up to 8-1/2" in length

Fits around third brake light when expanded

Model DL16V-CV fits around Crown Vic's third brake light when expanded

Crown Vic mounting bracket included

Height adjustable from 1/2" to 1-1/4" above rear deck

Non-reflective powder coated aluminum housing

4 Synchronized flashing heads

The DL16 offers computer designed optics maximizing the LEDs output

35 Customer selectable flash patterns

Hi/Low - Day/Night mode

Current limit protection over entire operating voltage

Reverse polarity protected: 10V-16V DC

Amp draw: DL16V: 1.0 Amps

DL16: 3.2 Amps

Dimensions (without mounting brackets):

1-7/8"H x 14-5/16"L x 5-3/4"D

Weight: 3 lbs.

Standard 15' cable (custom lengths available)

4-Conductor cable: Hi/Low, Pattern Select, Ground, +12V DC

Color combinations: Red, Blue, Amber, Green and White

Approvals: SAE J595, SAE J1318, and California Title 13 for Red & Blue

REAR LED LIGHT SYSTEMS

DL16-6/CV & DL16V-6/CV 6-HEAD ADJUSTABLE REAR LED LIGHT SYSTEMS



**DL16V-6
STANDARD LED'S**



**DL16-6
HIGH INTENSITY GEN-3 LED'S**



THE DL16V-6 SERIES IS EXPANDABLE UP TO 8 1/2" IN LENGTH!

Interior mount only to any vehicles rear window deck

Flashback hood

Expandable up to 8-1/2" in length

Fits around third brake light when expanded

Model DL16V-6CV fits around Crown Vic's third brake light when expanded

Crown Vic mounting bracket included

Height adjustable from 1/2" to 1-1/4" above rear deck

Non-reflective powder coated aluminum housing

4 Synchronized flashing heads

The DL16 offers computer designed optics maximizing the LEDs output

35 Customer selectable flash patterns

Hi/Low - Day/Night mode

Current limit protection over entire operating voltage

Reverse polarity protected: 10V-16V DC

Amp draw: DL16V: 1.0 Amp, DL16-6 1.6 amps

DL16: 3.2 Amps

Dimensions (without mounting brackets):

1-7/8"H x 20-1/2"L x 5-3/4"D

Weight: less than 4 lbs.

Standard 15' cable (custom lengths available)

4-Conductor cable: Hi/Low, Pattern Select, Ground, +12V DC

Color combinations: Red, Blue, Amber, Green and White

Approvals: SAE J595, SAE J1318, and California Title 13 for Red & Blue