

## 20011

### FEATURES

- ♦ LED - 360° beacon, 20' cable and on/off switch
- ♦ powder coated die-cast aluminum base
- ♦ enclosed bottom
- ♦ stainless steel clamp ring

### BENEFITS

- ♦ maintenance free, no bulbs to replace!
- ♦ low current draw 0.5 amps
- ♦ available in 12 or 24Vdc
- ♦ 3 selectable patterns with selectable switch: rotating, strobing and random sequences



*The environmental choice, low current draw, low maintenance, long LED life*

### APPLICATIONS

- ♦ suitable for indoor applications such as mines or pulp mills and underground vehicles
- ♦ surface mount and 1/2" NPT conduit mount
- ♦ rated for -30°C to +70°C

### MODELS

20001	(120/240VAC, amber LED's)
20003	(120/240VAC, white LED's)
20005	(120/240VAC, red LED's)
20011	(12Vdc, amber LED's)
20013	(12Vdc, white LED's)
20015	(12Vdc, red LED's)
20021	(24Vdc, amber LED's)
20023	(24Vdc, white LED's)
20025	(24Vdc, red LED's)

### SPECIFICATIONS

Voltages	Amps	Approvals
12Vdc	0.5	CSA
24Vdc	0.5	CSA
120/240VAC	0.1	CSA

### MEASUREMENTS

Height .....5 1/2"  
Width .....5 3/4"

### REPLACEMENT PARTS

Outer Dome Amber .....877401  
Outer Dome Clear .....877403  
Clamp Ring .....365

### LED COLOURS

 Amber  
 Red  
 White