

## 200E & E-1 (ULC LISTED)

### FEATURES

- ♦ high profile industrial strobe light
- ♦ anodized aluminum case
- ♦ fully encapsulated circuitry

### BENEFITS

- ♦ can be ULC approved in certain colours and voltages
- ♦ weather and corrosion resistant (model I200E)
- ♦ fused for reverse polarity protection

### APPLICATIONS

- ♦ suitable for indoor industrial applications (model 200E-1) such as assembly lines and deaf institutions or indoor/outdoor industrial applications (model 200E) such as oil drilling rigs or burglar alarm systems, fire alarm systems



### APPLICATIONS CONT.

- ♦ surface mount and 3/4" NPT conduit mount (standard for model 200E), octagon box mount (standard for model 200E-1)

*Note:  
surge suppression available for certain applications*

### MODELS

200E-24V-Colour	(24Vdc, single flash, specify colour)
200E-120V-Colour	(120 VAC, single flash, specify colour)
200E-1-24V-Colour	(24Vdc, single flash, specify colour)
200E-1-120Colour	(120VAC, single flash, specify colour)

### SPECIFICATIONS

Voltages	Amps	Joules	Approvals
24Vdc	1.2	10-14 ☒	ULC Listed
120VAC	0.1	10-14 ☒	ULC Listed

☒ depending on flash pattern chosen (single or double)

### MEASUREMENTS

Height	.....7 1/4"
Width	.....7 5/8"

### REPLACEMENT PARTS

Polycarbonate Lens	.....300
Strobe tube	.....129
Power Supply	.....181-12V
Power Supply	.....181-72V
Power Supply	.....181-120V
Power Supply	.....181-240V
Power Supply	.....181-24V-ULC (24Vdc ULC model - 4 leads)
Power Supply	.....181-120V-ULC (120VAC ULC model - 4 leads)
Power Supply	.....181-240V
Head Assembly	.....180 (single flash head)
Head Assembly	.....180D (double flash head)
Base Rubber	.....111
Bottom Plate	.....104-S (specify model 200E or 200E-1)

### LENS COLOURS

	Amber
	Red
	Clear