

**MEASUREMENTS**

Height .....7 1/2"  
 Width .....6 5/8"  
 Width Across Flange .....7 3/4"

**REPLACEMENT PARTS**

Lens amber .....300-A  
 Lens clear .....300-C  
 Lens red .....300-R  
 Strobe tube .....129  
 Power Supply .....181-12V  
 Power Supply .....181-72V  
 Power Supply .....181-120V  
 Power Supply .....181-240V  
 Head Assembly (single flash head) .....180  
 Head Assembly (double flash head) .....180D  
 Stainless Guard .....274S

**FEATURES**

- ♦ durable, flange mount strobe light
- ♦ stainless steel base and guard
- ♦ enclosed bottom
- ♦ fully encapsulated circuitry

**BENEFITS**




- ♦ fused for reverse polarity protection
- ♦ weather and corrosion resistant
- ♦ guard prevents lens breakage

*customer must drill egress hole  
 surge suppression available for  
 certain applications*

**APPLICATIONS**

- ♦ suitable for heavy duty applications shipping, mining etc.
- ♦ flange mount
- ♦ rated for -30°C to +70°C

**LENS COLOURS**

Amber   
 Red   
 Clear 

**29 SERIES**



**MODELS**

29001	(12-48Vdc, single flash, stainless, amber lens)
29006	(12-48Vdc, double flash, stainless, amber lens)
29021	(72-125Vdc, single flash, stainless, amber lens)
29026	(72-125Vdc, double flash, stainless, amber lens)
29041	(120VAC, single flash, stainless, amber lens)
29051	(120VAC, double flash, stainless, amber lens)
29061	(240VAC, single flash, stainless, amber lens)
29071	(240VAC, double flash, stainless, amber lens)
29003	(12-48Vdc, single flash, stainless, clear lens)
29008	(12-48Vdc, double flash, stainless, clear lens)
29023	(72-125Vdc, single flash, stainless, clear lens)
29028	(72-125Vdc, double flash, stainless, clear lens)
29043	(120VAC, single flash, stainless, clear lens)
29053	(120VAC, double flash, stainless, clear lens)
29063	(240VAC, single flash, stainless, clear lens)
29073	(240VAC, double flash, stainless, clear lens)
29005	(12-48Vdc, single flash, stainless, red lens)
29010	(12-48Vdc, double flash, stainless, red lens)
29025	(72-125Vdc, single flash, stainless, red lens)
29030	(72-125Vdc, double flash, stainless, red lens)
29045	(120VAC, single flash, stainless, red lens)
29055	(120VAC, double flash, stainless, red lens)
29065	(240VAC, single flash, stainless, red lens)
29075	(240VAC, double flash, stainless, red lens)

**SPECIFICATIONS**

Voltages	Amps	Joules	Approvals
12-48Vdc	2.5	10-14 ⌘	CSA
72-125Vdc	0.5	10-14 ⌘	CSA
120VAC	0.1	10-14 ⌘	CSA
240VAC	0.1	10-14 ⌘	CSA

⌘ depending on flash pattern chosen (single or double)