

## I200J & J-1

### FEATURES

- ♦ durable, compact low profile strobe light
- ♦ powder coated, die cast aluminum case
- ♦ fully encapsulated circuitry
- ♦ stainless steel clamp ring

### BENEFITS

- ♦ easy field servicing
- ♦ available in single flash only, 65 ± 5 fpm
- ♦ weather and corrosion resistant
- ♦ outer dome keeps inner lens dirt free and cleans easily

### APPLICATIONS

- ♦ suitable for indoor/outdoor applications including forklifts, tow motors, assembly line malfunction warning systems, restricted areas, high danger areas and calling systems
- ♦ surface mount, 1/2" NPT conduit mount or two knockout holes to accommodate octagon box
- ♦ rated for -30°C to +70°C

### MODELS

I200J-12V-Colour	(12Vdc, single flash, specify colour)
I200J-24V-Colour	(24Vdc, single flash, specify colour)
I200J-36V-Colour	(36Vdc, single flash, specify colour)
I200J-120V-Colour	(120VAC, single flash, specify colour)
I200J-240V-Colour	(240VAC, single flash, specify colour)
I200J-1-12-Colour	(12Vdc, single flash, outer dome, specify colour)
I200J-1-24-Colour	(24Vdc, single flash, outer dome, specify colour)
I200J-1-36-Colour	(36Vdc, single flash, outer dome, specify colour)
I200J-1-120Colour	(120VAC, single flash, outer dome, specify colour)
I200J-1-240Colour	(240VAC, single flash, outer dome, specify colour)

### SPECIFICATIONS

Voltages	Amps	Joules	Approvals
12Vdc	0.5	3	CSA
24Vdc	0.3	3	CSA
36Vdc	0.2	3	CSA
120VAC	0.1	3	CSA
240VAC	0.1	3	CSA



Model I200J-1

Model I200J

**Note:**  
I200J-1 model comes complete with clear outer dome

### MEASUREMENTS

Height (200J-1)	.....7 1/8"
Height (200J)	.....6"
Width	.....6"

### REPLACEMENT PARTS

Polycarbonate Outer Dome	.325
Polycarbonate Inner Lens	...333
Strobe tube	.....129-Z
Power Supply	.....181-Z-Specify (available in 12, 24, 36Vdc and 120, 240VAC)
Stainless Clamp Ring	.....4122

### LENS COLOURS

	Amber
	Red
	Clear