

I200U/U-1 & I200UH

FEATURES

- ♦ medium profile industrial strobes with or without horn
- ♦ cast zinc base
- ♦ polycarbonate fresnel lens
- ♦ model I-200UH horn rated for, 101dB rating at 30cm



BENEFITS

- ♦ effective dual warning system: sound and visibility in one product! (model I200UH)
- ♦ easy field servicing
- ♦ fully encapsulated circuitry
- ♦ heavy duty, weather and corrosion resistant
- ♦ fused for reverse polarity protection

*Note:
strobe model available with outer polycarbonate dome model I-200U-1*

APPLICATIONS

- ♦ suitable for industrial assembly lines, equipment malfunction warning systems, security intrusions and any industrial or commercial applications requiring a durable strobe with or without additional audible warning
- ♦ surface mount, 1/2" NPT conduit mount or two knockout holes to accommodate octagon box
- ♦ rated for -30°C to +70°C

MODELS

I200U-120V-Colour	(120VAC, single flash, specify colour)
I200U-1-120Colour	(120VAC, single flash, specify colour)
I200UH-120-Colour	(120VAC, single flash, horn, specify colour)

SPECIFICATIONS

Voltages	Amps	Joules	Approvals
120VAC (I-200U)	0.1	10	CSA
120VAC (I-200UH)	0.1	10	CSA

MEASUREMENTS

I200U Height 5 5/8"
I200U Width6"
I200U-1 Height6 3/4"
I200U-1 Width6"
I200UH Height7 3/8"
I200UH Width6"

REPLACEMENT PARTS

Polycarbonate Outer Dome	.325
Polycarbonate Inner Lens	.. .333
Strobe tube129-U
Power Supply181-U
Stainless Clamp Ring4122

LENS COLOURS

-  Amber
-  Red
-  Clear