

**MEASUREMENTS**

Height .....4"  
 Width .....4 1/8"

**REPLACEMENT PARTS**

Polycarbonate Lens .....330  
 Strobe tube .....129-Z  
 Power Supply .....181 -Z-Specify  
 (available in 12, 24 or 36Vdc and 120 or 240VAC)  
 Clamp Ring .....374-Z

**I200Z**

**FEATURES**

- ♦ best selling low profile industrial strobe light
- ♦ powder coated, die cast aluminum case
- ♦ fully encapsulated circuitry
- ♦ aluminum clamp ring

**BENEFITS**

- ♦ easy field servicing
- ♦ available in single flash only, 65 ± 5 fpm
- ♦ weather and corrosion resistant

**APPLICATIONS**

- ♦ suitable for tow motors, assembly line malfunctions, automatic door systems, alarm systems and calling stations eg. nursing stations
- ♦ surface mount and 1/2" NPT conduit mount
- ♦ rated for -30°C to +70°C



Model I200Z shown in application on industrial equipment

**MODELS**

I200Z-12V-Colour	(12Vdc, single flash, specify colour)
I200Z-24V-Colour	(24Vdc, single flash, specify colour)
I200Z-120V-Colour	(120VAC, single flash, specify colour)
I200Z-240V-Colour	(240VAC, single flash, specify colour)

**SPECIFICATIONS**

Voltages	Amps	Joules	Approvals
12Vdc	0.5	3	CSA, Class I Div II, NEMA 4X
24Vdc	0.3	3	CSA, Class I Div II, NEMA 4X
120VAC	0.1	3	CSA, Class I Div II, NEMA 4X
240VAC	0.1	3	CSA, NEMA 4X

**LENS COLOURS**

- Amber 
- Red 
- Clear 