

**MEASUREMENTS**

Height .....7 1/8"  
 Width .....6"

**REPLACEMENT PARTS**

Polycarbonate Outer Dome .325  
 Bulb (12V halogen) .....2073-796  
 Bulb (24V incandescent) ...2073-1638  
 Bulb (36V incandescent) ...2073-1062  
 Bulb (48V incandescent) ...2073-10498  
 Bulb (VAC halogen) .....2073-796  
 Complete Rotator Assembly 920-99  
 (comes with reflector and bulb)  
 Rotator Assembly .....920-98  
 Motor .....920-5  
 Worm Gear .....920-27  
 (white)  
 Worm Gear .....920-27F  
 (black worm gear for fast rotator)  
 Clamp ring .....4122  
 Rotator reflector .....920-1

**I20RH**

**FEATURES**

- ♦ economical rotator beacon light with powerful 35 watt halogen bulb (model I-20RH in 12Vdc, 120VAC and 240VAC) 24, 36 and 48V incandescent bulbs (model I-20RI)
- ♦ 85 rotations per minute
- ♦ powder coated die cast aluminum base
- ♦ stainless steel clamp ring



**BENEFITS**

- ♦ easy field servicing
- ♦ lightweight

**APPLICATIONS**

- ♦ suitable for tow motors, forklifts, assembly line malfunction warning systems, and hazard areas
- ♦ surface mount, 1/2" NPT conduit mount or two knockout holes to accommodate octagon box
- ♦ exceeds SAE low temperature requirements



Model I20RH shown in application on industrial equipment

**MODELS**

I20RH-12V-Colour (12Vdc, specify colour)  
 I20RH-24V-Colour (24Vdc, specify colour)  
 I20RH-120V-Colour (120VAC, specify colour)

**SPECIFICATIONS**

Voltages	Amps	Watts	Candlepower ∅	Approvals
12Vdc	3.0	35	60 ∅	CSA
24Vdc	1.0	24	32 ∅	CSA
120VAC	0.3	35	60 ∅	CSA

∅ candlepower specs provided by bulb manufacturer  
 ∅ minus reflector

**DOME COLOURS**

Amber   
 Red   
 Clear 