

Rear LED Light Systems

DL16/CV & DL16V/CV 4-Head Adjustable Rear LED Light Systems



DL16V
Standard LED's



DL16
High Intensity Gen-3 LED's



The DL16 Series is Expandable up to 8 1/2" in Length!

- # Interior mount only to any vehicles rear window deck
- # Flashback hood
- # Expandable up to 8-1/2" in length
- # Fits around third brake light when expanded
 - Model DL16V-CV fits around Crown Vic's third brake light when expanded*
 - Crown Vic mounting bracket included*
- # Height adjustable from 1/2" to 1-1/4" above rear deck
- # Non-reflective powder coated aluminum housing
- # 4 Synchronized flashing heads
- # The DL16 offers computer designed optics maximizing the LEDs output
- # 35 Customer selectable flash patterns
- # Hi/Low - Day/Night mode
- # Current limit protection over entire operating voltage
- # Reverse polarity protected: 10V-16V DC
- # Amp draw: DL16V: 1.0 Amps
DL16: 3.2 Amps
- # Dimensions (without mounting brackets):
1-7/8"H x 14-5/16"L x 5-3/4"D
- # Weight: 3 lbs.
- # Standard 15' cable (custom lengths available)
- # 4-Conductor cable: Hi/Low, Pattern Select, Ground, +12V DC
- # Color combinations: Red, Blue, Amber, Green and White
- # Approvals: SAE J595, SAE J1318, and California Title 13 for Red & Blue

Rear LED Light Systems

DL16-6/CV & DL16V-6/CV 6-Head Adjustable Rear LED Light Systems



DL16V-6
Standard LED's



DL16-6
High Intensity Gen-3 LED's



The DL16V-6 Series is Expandable up to 8 1/2" in Length!

- # Interior mount only to any vehicles rear window deck
- # Flashback hood
- # Expandable up to 8-1/2" in length
- # Fits around third brake light when expanded
Model DL16V-6CV fits around Crown Vic's third brake light when expanded
Crown Vic mounting bracket included
- # Height adjustable from 1/2" to 1-1/4" above rear deck
- # Non-reflective powder coated aluminum housing
- # 4 Synchronized flashing heads
- # The DL16 offers computer designed optics maximizing the LEDs output
- # 35 Customer selectable flash patterns
- # Hi/Low - Day/Night mode
- # Current limit protection over entire operating voltage
- # Reverse polarity protected: 10V-16V DC
- # Amp draw: DL16V: 1.0 Amp, DL16-6 1.6 amps
DL16: 3.2 Amps
- # Dimensions (without mounting brackets):
1-7/8"H x 20-1/2"L x 5-3/4"D
- # Weight: less than 4 lbs.
- # Standard 15' cable (custom lengths available)
- # 4-Conductor cable: Hi/Low, Pattern Select, Ground, +12V DC
- # Color combinations: Red, Blue, Amber, Green and White
- # Approvals: SAE J595, SAE J1318, and California Title 13 for Red & Blue