



HALOGEN FLASHERS



FM3669C



DRL366-1

SOLID STATE FLASHERS

Models & Specifications:

- FM3666:** 12V DC Mechanical Flasher.
Flash Rate: 1.2 flashes per second per lamp.
- FM3661:** 12V DC Solid state flasher for up to 100 Watts per side.
Flash Rate: 1.9 flashes per second per lamp.
- FM3662:** 12V DC Solid state flasher for up to 100 Watts per side.
Flash Rate: 2.9 flashes per second per lamp.
- FM3662-24:** 24V DC Solid state flasher for up to 100 Watts per side.
Flash Rate: 2.9 flashes per second per lamp.
- FM3667:** 12V DC Solid state flasher for back-up/brake light.
Flash Rate: 2.4 flashes per second per lamp.
- FM3669:** 12V DC Solid state flasher for up to 165 Watts per side.
Customer selectable flash patterns. DRL control.
- FM3669C:** 12V DC Solid state flasher for up to 165 Watts per side.
Customer selectable flash patterns.
Compatible with factory installed DRL control.
- FM6901:** 12V DC Solid state flasher. Alternately flashes headlights.
Has high beam override and night time cut off.
Handles up to 165 watts per output.
Flash Rate: 1.9 flashes per second per lamp.
- FM6902:** 12V DC Solid state flasher. Alternately flashes headlights.
Has high beam override and night time cut off.
Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.
- FM6903:** 12V DC Solid state flasher. Simultaneously flashes headlights.
Has high beam override and night time cut off. Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.
- FM6904:** Flashes left headlight three times, flashes right headlight three times, then flashes both headlights together three times. Handles up to 165 watts per output.
Flash Rate: 2.9 flashes per second per lamp.
- DRL366:** Daytime running light module.
- DRL366-1:** Heavy-duty daytime running light module with taillight output, park brake override.



FM3666

HALOGEN FLASHERS