



MOTORCYCLE ACCESSORIES

16873 LOW PROFILE MINI LIGHT BAR



- H: 3 5/8" W: 16 1/4" D: 8 3/8"
- Input: 12Vdc
- Current Draw: 0.9 - 2.0 amps
- 25 flash patterns
- Polycarbonate dome
- Permanent mounting (T-slot)
- Anodized, extruded aluminum base
- 8 high density encapsulated LED panels (45 LED's per panel)
- Encapsulated mother-board
- Polarity-protected
- Corrosion resistant
- Vibration resistant
- 100,000 hours LED rating
- On/Off switch supplied

MODEL 242SL STROBE WITH TP4000 TELESCOPIC POLE



242SL Strobe with TP4000

The 242SL strobe is a pipe mount, quad flash or selectable random flash strobe designed for mounting on our TP4000 telescopic pole. The 242SL series strobes are standard quad flash or field selectable random flash. The TP4000 telescopic pole extends to 48".

SPECIFICATIONS

Size	5.5" Dia. / 4" H (242SL Strobe)
Weight	1.5 Lbs. (242SL Strobe)
Voltage	12-24 Vdc (242SL Strobe)
Amps	2 Amps Max (242SL Strobe)
Size	1" Dia. / 28" to 48" L (TP4000 Pole)
Weight	1 Lb. (TP4000 Pole)

MOTORCYCLE

