

REMOTE POWER

REMOTE POWER SUPPLY SPECIFICATIONS

Model		RP310D	RP310Q	RP334**	RP341**	RP242**	RP244**	RP966**	RP996*	RP222W*	RP242W*
Power (Watts)		24	24	90	90	40	75	60	90	20	40
Amps	@12Vdc	2.5	2.5	8.6	8.6	4.2	7.8	7.8	9.4	2.2	4.4
	@24Vdc	1.3	1.3	4.3	4.3	2.1	3.9	3.1	4.7	1.1	2.2
Joules	Primary	7.8	7.8	12.5	12.5	3.4	6.4	5.5	8.3	5.0	10.1
	Secondary 1	3.5	3.1	6.0	6.0	3.4	6.4	3.8	5.7	2.0	3.9
	Secondary 2	N/A	3.1	6.0	6.0	3.4	6.4	3.8	5.7	2.0	3.9
	Secondary 3	N/A	3.1	6.0	6.0	3.4	6.4	3.8	5.7	2.0	3.9
	Secondary 4	N/A	N/A	N/A	N/A	3.4	6.4	3.8	5.7	N/A	N/A
Total Output Joules		11.3	17.1	30.5	30.5	17.0	31.9	20.7	31.1	10.9	21.8
Energy Efficiency		80%	80%	87%	87%	80%	80%	80%	80%	75%	75%
Number of Outlets		2	2	4	4	2	4	6	6	2	2
	Alternating Simultaneous	1&2 N/A	1&2 N/A	1&2,3&4 1&4,2&3	1&2,3&4 1&4,2&3	1&2 N/A	1&3,2&4 1&2,3&4	1&2,3&4,5&6 1,2,3,4,5,6	1&2,3&4,5&6 1,2,3,4,5,6	1&2 1&2	1&2 1&2
High/Low Power Option		Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Head-Switching Option				Order SA or SS	Yes	Yes	Yes	Yes	Yes	Yes	Yes
	SA=Alternating SS=Simultaneous	N/A	N/A								
Fuse Protect		N/A	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Flash Rate		512fpm	672fpm	1410fpm	1410fpm	705fpm	1410fpm	2610fpm	2610fpm	440fpm	440fpm
Pattern Select		N/A	N/A	N/A	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Weatherproof		N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A	Yes	Yes
Weight (lbs.)		1.0	1.0	2.8	2.8	1.5	1.5	1.3	1.3	1.5	2.1

* Specs listed are for the quad flash pattern of these remote power supplies

** Specs listed are for the five flash pattern of these remote power supplies. Other patterns are customer selectable

One joule assimilates 100,000 candle power

All remote strobe paks are reverse polarity protected

CABLE SPECIFICATIONS FOR REMOTE POWER SUPPLIES

Model Number	Length	Light-Duty	Heavy-Duty	Shielded	Connector Pack Side	Connector Head Side
4415	15 ft.	X		X	Amp	Amp
4420	20 ft.	X		X	Amp	Amp
4425	25 ft.	X		X	Amp	Amp
4430	30 ft.	X		X	Amp	Amp
3814	specify*		X		Amp	Weatherproof
3820	specify*	X			Amp	Weatherproof
3821	specify*	X			Amp	Amp
3830	specify*		X		Weatherproof	Weatherproof

*Available in 5' increments (10'-50')